

UNICORN V2



When everything has been done and everything has been seen, we bring you the first ever 100% analog signal path Uni-vibe* Photocell Modulator w/ Tap Tempo.

Controls

Volume - Controls output volume.

Depth - Controls intensity of the effect. Left is less, right is more.

Speed - Controls rate/speed of the modulation. Left is slower, right is faster. Will override tap tempo speed when rotated.

Ratio - Controls the ratio of the tapped speed. Choose quarter, dotted eighth, eighth, or triplet notes. This allows for faster speeds with fewer taps.

dry/wet Toggle - Dry mode is the classic Univibe sound, while Wet is a vibrato sound.

Jacks

INPUT - 1/4" jack on the top right receives your instrument's signal.

OUTPUT - 1/4" jack on the top left sends the signal out of the pedal to an amplifier or pedal chain.

TAP/EXP - 1/4" jack on the right side of the pedal. In expression mode, connect any TRS expression pedal to control the pedal's speed. In tap mode, connect an external tap tempo controller or another pedal that receives tap tempo to use the Unicorn to slave the other pedal. Choose which one you want by the switch on the left side of the pedal.

Switches

BYPASS - Left footswitch turns the pedal on and off.

TAP TEMPO - Right footswitch taps in the speed of the mod-ulation.

INTERNAL TAP/EXP SWITCH - Internal switch lets you choose between tap or expression mode for the TAP/EXP jack.

POWER - Uses 9V DC Negative Center. Do not use more than 9V DC. Your warranty will be voided. 100mA max consumption.