



GA-5 Delay Rechargeable Mini Headphone Amp

Quick Start

Operation:

- Plug the 6.35 mm jack plug directly into the socket on your guitar.
- Plug a pair of headphones into the "Phones" port.
- Switch the slider on the GA-5 from STANDBY to ON (LED lights up) and start playing. Adjust the volume using the volume control on the instrument.
- You can connect an external audio source via AUX, e.g. to accompany a background track. Adjust the volume of the external audio signal using the volume control on the playback device.

Controls:

- **ECHO:** determines the proportion of delay signal and unprocessed signal
- **F.BACK:** (Feedback) determines the number of delay repetitions
- **TIME:** sets the delay time
- **STANDBY / ON** switch: Standby = device off (no signal) / ON = device on (LED illuminated)

Charging:

- The GA-5 must be charged when the sound quality deteriorates or the LED goes out.
- Switch off the device and connect it to a mobile phone charger or the USB socket of a computer using the USB cable supplied. The LED lights up during charging. The device is fully charged, when the LED goes out.
- Fully charge the device before not using it for an extended period of time.

Specifications:

Connections:

- Input: 6,35 mm (1/4") mono jack - plugs direct into the guitar
- Phones: 3,5 mm stereo jack - connection for headphones, mixer or active speakers
- USB: USB Mini-B port for charging cable
- Aux: 3,5 mm stereo jack - connection for external audio source (e.g. phone, tablet, PC ...)

Power supply:

- Rechargeable battery 380 mAh
- Battery life: ~ 4 hours

Laden:

- USB power adapter 5 V / min. 500 mA (e.g. phone charger) - not included
- USB-A to USB-Mini-B charging cable included
- charging current: ~ 210 mA
- charging time: ~ 2,5 h

Dimensions: 81 x 75 x 15.5 mm (W x D x H)

Weight: 52.3 g (incl. USB cable)